



EXIT SIGN

STANDARD PC IP 65

EXIT SIGN

STANDARD PC IP 65

WALL / CEILING



SPECIFICATIONS :

| | |
|-----------------------|--|
| Mounting | : Ceiling mounted (wall) |
| Lamp configuration | : 8W T5 |
| Lamp holder | : G5 |
| Control gear type | : EM Backup Kit HF Electronic Ballast |
| Operating mode | : Maintain / Non Maintain |
| Voltage rating/ freq. | : 220-240V / 50-60 Hz |
| Degree of protection | : IP 65 |
| Internal wiring | : 0.5 mm sq solid copper wire PVC 105 deg C |
| Cable entry | : Side or rear cable entry |
| Cable connection | : Terminal block, 3-pole, screw type |
| Conformity | : IEC 60598 / SASO 1318 |

DESCRIPTIONS : EXITEK STANDARD PC IP 65 is a wall/ceiling mounted exit/emergency light of polycarbonate Housing with Maintained (M) and Non-Maintained (NM) 3 hrs Emergency Kit (1.5 Hr. as option). This type is suitable for all types of walls and ceilings.


APPLICATIONS : Schools, offices and passages, hospitals, parking and malls

| CODE | L | W | H | CODE | L | W | H |
|--|-----|-----|-----|--|-----|-----|-----|
| EXIT [WAL/PC] M-3hr T5-1X8W - ARABIC/ENGLISH [WH] [IP65] | 348 | 110 | 168 | EXIT [CEIL/PC] NM-3hr T5-1X8W - ARABIC/ENGLISH [WH] [IP65] | 348 | 110 | 168 |
| EXIT [WAL/PC] M-3hr T5-1X8W - ARROW UP [WH] [IP65] | 348 | 110 | 168 | EXIT [CEIL/PC] NM-3hr T5-1X8W - ARROW UP [WH] [IP65] | 348 | 110 | 168 |
| EXIT [WAL/PC] M-3hr T5-1X8W - ARROW DOWN [WH] [IP65] | 348 | 110 | 168 | EXIT [CEIL/PC] NM-3hr T5-1X8W - ARROW DOWN [WH] [IP65] | 348 | 110 | 168 |
| EXIT [WAL/PC] M-3hr T5-1X8W - ARROW LEFT [WH] [IP65] | 348 | 110 | 168 | EXIT [CEIL/PC] NM-3hr T5-1X8W - ARROW LEFT [WH] [IP65] | 348 | 110 | 168 |
| EXIT [WAL/PC] M-3hr T5-1X8W - ARROW RIGHT [WH] [IP65] | 348 | 110 | 168 | EXIT [CEIL/PC] NM-3hr T5-1X8W - ARROW RIGHT [WH] [IP65] | 348 | 110 | 168 |
| EXIT [WAL/PC] M-3hr T5-1X8W - NO ARROW [WH] [IP65] | 348 | 110 | 168 | EXIT [CEIL/PC] NM-3hr T5-1X8W - NO ARROW [WH] [IP65] | 348 | 110 | 168 |

OPTIONS:

- Emergency duration for 1.5 Hrs.
- High frequency (HF) electronic control gear for central battery systems (CBS) compatibility

Ordering Example



Head office

Malaz - Salahidin Road
P.O Box 1246 Riyadh 11431

Tel : +966 11 477 77 00
Fax: +966 11 478 94 69

Western Region Office

Tahliya Street
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888
Fax: +966 12 6633413

Eastern Region Office

King Abdulaziz Street
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509
Fax: +966 13 8329065

ContactUs@noortek.com



www.noortek.com