



**WALLUX**  
WL05X SERIES

# OUTDOOR

WALLUX

WL05X SERIES





## SPECIFICATIONS :



Housing	: Die-cast aluminum
Lamp Type	: MH/CFL
Lamp holder	: E27/G24
Voltage rating/ freq.	: 220-240V / 50-60 Hz
Control gear type	: HPF conventional control gear HF electronic control gear
Power factor	: >0.9
Degree of protection	: IP 65
Optical configuration	: Anodized aluminium reflector
Finishing	: UV stabilized polyester powder coating, resistant to corrosive environment.
Light controller	: Clear tempered glass diffuser

**DESCRIPTIONS :** WALLUX WL05X Series is a round wall mounted up/down light luminaires for outdoor applications. Using of high quality die cast aluminium housing and tempered glass diffuser make this product suitable for the most severe conditions with protection degree IP 65.

**APPLICATIONS :** Facade lighting, entrance, gates and other similar outdoor applications.



CODE	D	H
WALLUX [WL051]-18/26W TC-D	160	360
WALLUX [WL051]-35W MH	160	360
WALLUX [WL051]-70W MH	160	360
WALLUX [WL051]-150W MH	160	360



CODE	D	H
WALLUX [WL055]-2x18/26W TC-D	160	560
WALLUX [WL056]-2x35W MH	160	560
WALLUX [WL057]-2x70W MH	160	560
WALLUX [WL058]-2x150W MH	160	560

### **Head office**

Malaz - Salahidin Road  
P.O Box 1246 Riyadh 11431

Tel : +966 11 477 77 00  
Fax: +966 11 478 94 69

### **Western Region Office**

Tahliya Street  
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888  
Fax: +966 12 6633413

### **Eastern Region Office**

King Abdulaziz Street  
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509  
Fax: +966 13 8329065

ContactUs@noortek.com



**www.noortek.com**