



FLOODLUX

F03X SERIES



SPECIFICATIONS :

Housing	: Die-cast aluminium
Lamp Type	: Halogen / metal halide
Lamp holder	: GU5.3/G12/ E40
Voltage rating/ freq.	: 220-240V / 50-60 Hz
Control gear type	: HF electronic transformer HPF conventional control gear
Power factor	: >0.9
Degree of protection	: IP 65
Optical configuration	: High purity anodized aluminium reflector
Finishing	: UV stabilized polyester powder coating, resistant to corrosive environment.
Seal	: Silicon gasket and silicone sealant, able to withstand the temperature up to 220C.
Glass	: 4 mm thickness tempered safety glass with stainless steel screws

DESCRIPTIONS : FLOODLUX F03X Series of rotatable professional projector provides unique solution for architectural building entrance and concrete/steel building louvers. Using of high quality die cast aluminium housing and protection glass make this product suitable for the most severe conditions with protection degree IP 65.

APPLICATIONS : Architectural details, high lighting signs and logo panels and other similar applications.





OUTDOOR

FLOODLUX

F03X SERIES

SPECIFICATIONS :



Lamp Configuration	: 50W LV Halogen/20W MH
Lamp holder	: GU5.3 / G8.5
Beam Angle	: 10°/24°/45°
Light Controller	: Pure Aluminium Reflector
Input Voltage	: 220V / 60 Hz
Control gear	: HF electronic transform 12Vac Electronic MH ballast 20W



CODE	D	H
FLOODLUX [F031]-50W HAL	160	262
FLOODLUX [F032]-20W MH		

SPECIFICATIONS :



Lamp Configuration	: 35W MH / 70W MH
Lamp holder	: G12
Beam Angle	: 6°/20°
Light Controller	: Pure Aluminium Reflector
Input Voltage	: 220V / 60 Hz
Control gear	: HPF conventional control gear



CODE	D	H
FLOODLUX [F033]-35W MH	210	328
FLOODLUX [F034]-70W MH	210	328

SPECIFICATIONS :



Lamp Configuration	: 150W MH
Lamp holder	: G12
Beam Angle	: 6°
Light Controller	: Pure Aluminium Reflector
Input Voltage	: 220V / 60 Hz
Control gear	: HPF conventional control gear



CODE	D	H
FLOODLUX [F035]-150W MH	273	405

SPECIFICATIONS :

Lamp Configuration	: 250W MH / 400 MH
Lamp holder	: E40
Beam Angle	: 6°
Light Controller	: Pure Aluminium Reflector
Input Voltage	: 220V / 60 Hz
Control gear	: HPF conventional control gear



CODE	D	H
FLOODLUX [F036]-250W MH	363	550
FLOODLUX [F037]-400W MH	363	550

Head office

Malaz - Salahidin Road
P.O Box 1246 Riyadh 11431

Tel : +966 11 477 77 00
Fax: +966 11 478 94 69

Western Region Office

Tahliya Street
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888
Fax: +966 12 6633413

Eastern Region Office

King Abdulaziz Street
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509
Fax: +966 13 8329065

ContactUs@noortek.com



www.noortek.com